

In the Specification:

Page 7, after line 19, insert the following:

--Figure 7 is an exploded view of a portion of the

enlarged cross-section of the probe tip shown in Fig. 6.--

line 20, change "7" to --8--;

line 23, change "8" to --9--;

line 24, change "7" to --8--; and

after line 25, insert the following:

--Figure 10 is an end view of the probe tip of the catheter

in the direction 10-10 of Fig. 9.--

Page 8, line 1, change "Figure 9" to --Figures 11, 11a, 11b and 11c--, and change "is a schematic diagram" to --are schematic diagrams--.

N.B. Page 19, line 24, change "60-68" to--160-168--.

N.B. Page 20, line 1, change "60" to--160--;

N.B. Line 4, change "62" to--162--;

N.B. Line 5, change "64" to--164--;

N.E. Line 8, change "68" to--168--; and

N.E. Line 10, change "60-68" to--160-168--.

N.B. Page 21, line 21, change "58" to--158--.

N.E. Page 22, line 2, change "62" to--262--;

N.B. Line 3, change "62" to--262--;

N.B. Line 4, change "60" to--260--;

N.E. Line 5, change "64" to--264--;

N.B. Line 11, change "64" to--264--; and

N.B. Line 17 change "its inner surface 62" to--the